

SPECTRA H10A

1024×768 HOT Cooled MWIR Module

Overview

A 10 μm , 1024×768 HOT cooled MWIR imaging module with a 144 mm athermalized lens, Camera Link output, ≤ 40 mK NETD, and compact 200×77×62 mm packaging.



1024×768

RESOLUTION


10 μm

PIXEL PITCH


 ≤ 40 mK

NETD


 $3.7\pm 0.2\text{--}4.8\pm 0.2$ μm

SPECTRAL RANGE

Key Features

Engineering profile

- The standard specification uses Camera Link video and RS422 command control.

Key capabilities

- Detector: HOT cooled MWIR
- Resolution: 1024×768 @ 25 ± 0.5 Hz
- Pixel pitch: 10 μm
- Spectral band: $3.7\pm 0.2\text{--}4.8\pm 0.2$ μm
- Thermal sensitivity: NETD ≤ 40 mK


Image processing and control

- White-hot and black-hot polarity, manual or automatic gain/contrast/brightness, edge enhancement, shutter or background non-uniformity correction, crosshair overlay, state retention, self-test, and 2× electronic zoom are available through serial control.

Typical Applications




Long-range Surveillance



Aerospace



Integrated EO/IR Systems



Environmental Protection



Technical Specifications

Detector & Optics

Detector	HOT cooled MWIR
Resolution	1024×768
Pixel pitch	10 μm
Spectral band	3.7±0.2–4.8±0.2 μm
Thermal sensitivity	NETD ≤40 mK
Lens configuration	144 mm athermalized, F/3.0
Field of view	≥4°×3°; distortion ≤3%
Focus range	200 m to infinity
Defective pixels	≤0.5%, no clusters in central area

Video & Interfaces

Video output	Camera Link
Control interface	RS422
Frame rate	25 ±0.5 fps
Recognition range	≥5 km (standard vehicle target)
Image processing	NUC, white/black-hot, AGC, edge enhancement, crosshair, 2× digital zoom
Optical-axis stability	≤0.1 mrad

Power & Physical

Power supply	DC 18–32 V
Power consumption	Average <12 W; start-up <22 W
Start-up / readiness	≤3 min typical; ≤6 min full temperature range
Dimensions	≤200×77×62 mm
Weight	≤0.8 kg
Operating temperature	–40 to +60 °C
Storage temperature	–50 to +70 °C
Continuous operation	≥8 h
MTBF	≥1200 h (mature stage)
Service life	≥10 years
Protection	Over-current & reverse-polarity

Specifications reflect the supplied technical document. Lens, connector, mechanical, and environmental options may be finalized for the target program.
Rev. 1.0 · September 2026